



AGGRETEx
DECORATIVE CONCRETE SURFACES


INSTALLATION INSTRUCTIONS



AggreTex is custom concrete that rocks! AggreTex utilizes a proprietary blend of cementitious materials, aggregates, and color to create beautiful monolithic concrete slabs for exterior and interior applications. It can be polished or exposed to provide a custom finish to your specification! AggreTex is designed to be installed by professional concrete contractors.

PACKAGING & COVERAGE

AggreTex is packaged in 50 lb. bags yielding about 10-12 sft. at 3/8". AggreTex should be stored in dry, covered areas between 50°-90° F. Shelf life is 12 months in unopened bags.



APPLICATION WET-ON-WET




AggreTex is supported by our patented wet-on-wet installation system. Base concrete should be placed to specification & all control joints should be honored. Screenshot base concrete 3/8" low and allow base concrete to achieve plastic state. Apply mixed AggreTex to plastic base concrete to achieve monolithic slab construction. Finish to specification!

MIXING

Each 50 lb. bag of AggreTex should be mixed with 3-3 1/2 quarts of water. Mix time is approximately 3 minutes to achieve "cake batter" consistency. Multiple bags can be mixed simultaneously following appropriate ratios. Check out installation videos on youtube to see it in action! Want to add decorative aggregate or glass? This truly makes AggreTex rock! When adding additional aggregates, do not exceed 40 lbs. per 50 lb. bag. A mock up sample should always be done to test aggregate exposure.



FINISH OPTIONS



Surface retarders can be applied to AggreTex per instructions to provide a consistent texture and appearance. Aggregates will be exposed creating a dynamic, slip resistant finish for interior or exterior applications. Apply sealers to specification to achieve appearance and functionality as desired. AggreTex slab should be fully cured in 14 days – keep free of heavy loads during curing.

AggreTex is also an ideal material for polishing in interior applications! Allow materials to cure for 36-48 hours prior to processing for best results. Polish to specification!



DO

read, observe and follow all precautions as outlined in AggreTex MSDS

DO

keep out of reach of children, wear suitable protective gear, avoid contact with the eyes, & wash exposed skin with soap & water

DO

insure there is sufficient ventilation when installation AggreTex or any other cementitious material. Wear proper respiratory gear as needed as AggreTex does contain materials known by the State of California to cause cancer, birth defect, or reproductive harm



DO NOT

use material if packaging is damaged.

Using opened bags will result in inconsistent mixing

DO NOT

forget to protect your finished surface from potential damage by other trades

DO NOT

install AggreTex into standing bleed water or onto concrete that is bleeding excessively

DO NOT

install in areas prone to acid exposure, heavy salt exposure or other materials known to aggressively deteriorate Portland cement based products

WARRANTY

AggreTex is warranted to be of uniform quality and consistency per manufacturing tolerances. Warranty is limited to purchase price of material deemed defective as control is not exercised over its use. No warranty, expressed or implied, is made to the effects of its use. Users assume all risks and liabilities resulting from the use of this product.

AggreTex is a registered trademark of AggreTex Systems, LLC.