AGGRETEX
DECORATIVE CONCRETE SOLUTIONS

AggretexSC, LLC
252 West Larch Rd., Suite A • Tracy, CA 95304

AGGRETEX™ SHINE MA

PRODUCT DATA SHEET

AGGRETEX SHINE MA - MATTE FINISH LACQUER BASED SEALER

DESCRIPTION

Aggretex SHINE MA is a lacquer sealer developed for interior and exterior applications to bring out the radiance and luster of exposed aggregate and other decorative concrete surfaces. Aggretex SHINE MA is ideal for stained concrete, exposed aggregate slabs, walkways,decks and walls.

Aggretex SHINE MA is formulated with a unique solvent blend allowing fast-drying, solvent-base performance along with VOC compliance in the OTC/LADCO/MRPO/SCAQMD regions.

FEATURES & BENEFITS

- Provides a crystal clear membrane for new or old concrete for improved durability.
- Seals all concrete surfaces, providing a glossy appearance and easier clean-up.
- Dust proofs concrete with a tough, durable film.
- Will not yellow under ultraviolet exposure.

SPECIFICATIONS & COMPLIANCES

- Complies with Federal AIM rule VOC requirements and VOC standards in OTC/LADCO/MRPO/ SCAQMD regions
- V.O.C. content < 100 g/l.

APPLICATION

Surface Preparation - The concrete surface must be clean and free of standing water. Remove any sealer or other material that may prevent adhesion of Aggretex SHINE.

Application to Fresh Concrete - Apply at a uniform coverage by spray at 250-350 sq ft /gal. Product may be sprayed with a hand held "pump-up" sprayer or an airless industrial sprayer. Best result are achieved when spray applied. If roller applied, use a short napped solvent resistant sleeve and avoid entrapping air (bubbles).

Aggretex SHINE MA should be agitated well before every use.

AGGRETEX™ SHINE MA

PRODUCT DATA SHEET

AGGRETEX SHINE MA - MATTE FINISH LACQUER BASED SEALER

Sealing Existing Concrete - the surface must be thoroughly cleaned and dried before applying Aggretex SHINE. Pressure washing with a strong alkaline detergent to remove dirt, waxes and oils is recommended. Acids will not sufficiently clean or remove dirt, curing compounds, or old sealer from concrete. Worn or porous areas may need a second application for uniform sealing and appearance. Allow 12 hours before 2nd application of sealer. In general, multiple thin coats (400 sft. / gal) will provide a harder, more durable finish than a single heavy application. Dry time will be influenced by both temperature and humidity.

PACKAGING

55 gallon drums (208.2 L)
5 gallon pails (18 L)
1 gallon cans (4 to a case) (3.8 L)

LIMITATIONS

- Agitate Aggretex SHINE MA well before every use
- Does not provide a base for cementitious materials.
- Treated surfaces may be slippery when wet with rain or other liquids.
- For best results apply when concrete surfaces or ambient temperatures are between 55°F (12.8°C) and 80°F (26.7°C)
- Use with adequate ventilation. Keep away from open flames.
- When sealing existing concrete, Aggretex SHINE may darken and highlight imperfections in hardened concrete surfaces, resulting in a mottled surface appearance. Prepare a test panel to ensure acceptable results.
- Do not apply in areas where there may be excessive internal water migration to the back of the film
- Do not dilute or alter in any way.
- Read the MSDS before using the product.

DO NOT EXPOSE TO OR APPLY NEAR FIRE OR FLAMES. FOR WELL VENTILATED OR EXTERIOR USE ONLY!

TECHNICAL SERVICES

For assistance, contact technical services at: 877.579.5886
www.aggretex.com

SHELF LIFE

Shelf life of Aggretex SHINE in the original tightly closed containers is 2 years from the date of manufacture. Do not allow the accumulation of water, dirt or other contaminants.

AGGRETEX SHINE MA - MATTE FINISH LACQUER BASED SEALER

WARRANTY

NOTICE-READ CAREFULLY
CONDITIONS OF SALE

AggretexSC, LLC offers this product for sale subject to and limited by the warranty which may only be varied by written agreement of a duly authorized corporate officer of AggretexSC, LLC. No other representative of or for AggretexSC, LLC is authorized to grant any warranty or to waive limitation of liability set forth below.

WARRANTY LIMITATION

AggretexSC, LLC warrants this product to be free of manufacturing defects. If the product when purchased was defective and was within use period indicated on container or carton, when used, AggretexSC, LLC will replace the defective product with new product without charge to the purchaser. AggretexSC, LLC makes no other warranty, either expressed or implied, concerning this product. There is no warranty of merchantability. NO CLAIM OF ANY KIND SHALL BE GREATER THAN THE PURCHASE PRICE OF THE PRODUCT IN RESPECT OF WHICH DAMAGES ARE CLAIMED.

INHERENT RISK

Purchaser assumes all risk associated with the use or application of the product.